

# СвАМц (Al-Mn)

Additional (metallurgy, welding)

## DESIGNATIONS

EN AW	ASTM / US	DIAMETERS	$\Sigma$ , MPA
<b>СвАМц (Al-Mn)</b>	—	<b>9.5; 12 mm</b>	<b>125</b>

## APPLICATIONS

Al-Mn welding wire — for welding aluminium-manganese alloy structures.

## ADVANTAGES

- Corrosion-resistant weld bead
- Good ductility
- Stable welding arc

## TEMPER STATES

TEMPER	DIAMETER, MM	TENSILE STRENGTH, MPA	ELONGATION, MIN, %	RESISTIVITY, MAX, $\Omega \cdot \text{MM}^2/\text{M}$	CONDUCTIVITY, MIN, % IACS
<b>O</b>	9.5; 12	125	25	—	—

## Alusilk

PART OF ITS GROUP

Coiled Aluminium · Connected Future

### HEADQUARTERS

Dubai Silicon Oasis, Dubai, UAE  
+971 50 153 0202  
info@alusilk.ae

### UZBEKISTAN BRANCH

7 Abdulla Qodiriy St · Yunusobod district ·  
Tashkent  
+998 97 341 2222  
alusilk.uz · alusilk.ae